



TECHNICAL DATA SHEET

ETCH PRIMER

Gerko Etch Primer is a super fast drying etching primer that gives the ultimate adhesion direct onto many difficult substrates including; alloy, stainless steel, zintec and galvanise. The final surface is a super smooth non-porous finish that is suitable for any topcoat.

PROPERTIES

- Outstanding etching properties
- Excellent anti-corrosive properties
- Fast drying and flexible primer
- Can be applied straight on bare metals
- Petrol resistant
- Super smooth finish
- Can be over painted with a wide range of other paints as alkyd-, cellulose-or epoxy based coatings

PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOUR	PIECES PER BOX	PIECES PER PALLET
AS060	Etch Primer 400 ml	Etch	12	1200

DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 15 min. Tack free ca. 30 min. Over paintable ca. 1 hour. Sandable ca. 1 hour.

DIRECTIONS BEFORE USE

- Use on room temperature
- Shake before use
- Surface must be dry, clean, free from dirt, rust, grease etc.
- Preferably the surface should be sanded lightly
- Spray cross wise layers
- Leave to evaporate/dry
- Sand the layer lightly for the best adhesion of the next layer
- After use, to clean the nozzle and prevent blockage: Hold the can up side down and spray until only gas is released

WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

APPLICATION TEMPERATURE, °C

- 15 - 30

STORAGE CONDITIONS

Cool (10°C - 20°C) and dry

SAFETY

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/ eye protection. Use only outdoors or in a well-ventilated area.